

# Eni i-Sint TD 10W-40



## APPLICATIONS

**Eni i-Sint TD 10W-40** is a synthetic technology lubricant designed to meet the needs of turbocharged diesel engines and commercial vehicles operating also in severe conditions.

## CUSTOMER ADVANTAGES

- The particular formulation of the product ensures adequate lubrication of metal surfaces even after prolonged periods of engine stop, thus facilitating the starts and reducing the wear effects even under very high load conditions.
- **Eni i-Sint TD 10W-40** has exceptional detergent-dispersing properties that inhibit the formation of black sludge on the relatively cooler engine parts and reduce the creation of lacquers and varnishes and other types of deposits.
- The presence of low volatility synthetic components and high thermal stability leads to a reduction in oil consumption.
- The thermo-oxidative properties give the product resistance to deterioration in operation, in conditions of prolonged exposure to high temperatures in the presence of air and other agents.

## SPECIFICATIONS

- ACEA A3/B4
- API CF/SH
- VW 505 00
- MB-Approval 229.3



# Eni i-Sint TD 10W-40



## CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	870
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	14.4
Viscosity Index	ASTM D 2270	-	155
Viscosity at -25°C	ASTM D 5293	mPa·s	5480
Flash point COC	ASTM D 92	°C	230
Pour point	ASTM D 97	°C	-33
B. N.	ASTM D 2896	mg KOH/g	10.8

